



### Main

Range of product	Canalis
Product name	KS
Product or component type	Adapter
Product compatibility	KS
[Ie] rated operational current	400 A
Colour	White (RAL 9001)

### Complementary

Accessory / separate part category	Adaptation
Device application	Adapt old offer
Mounting location	Between trunking
Mounting mode	By screws
Mounting support	Busbar
Busbar trunking polarity	3L + N + PE
Width	324 mm
Depth	95 mm
Height	188.5 mm
Body material	Plastic
Net weight	2.9 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
Standards	IEC 61439-6 IEC 60439-2

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.65 kg
Package 1 Height	10.6 cm
Package 1 width	19 cm
Package 1 Length	32.4 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	20
Package 2 Weight	138 kg
Package 2 Height	62 cm
Package 2 width	75 cm
Package 2 Length	92 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------

