



Main

Range of product	Canalis
Product name	KS
Product or component type	Blanking plate
Product compatibility	KS
[Ie] rated operational current	1000 A
Offer type	Spare part
Quantity per set	Set of 15

Complementary

Accessory / separate part category	Trunking accessory
Device application	Restore IP
Mounting location	On trunking
Mounting mode	By clips
Net weight	20 g

Environment

IP degree of protection	IP55 conforming to IEC 60529
Standards	IEC 61439-6 IEC 60439-2

Packing Units

Package 1 Weight	0.010 kg
Package 1 Height	0.040 dm
Package 1 width	0.690 dm
Package 1 Length	1.180 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------