Product data sheet Characteristics

LA9ZX01563 SPRING TERM 3P CONNECT MOD 16MM2 IEC/UL FOR 60 INTERAXIS BUSBAR





Main

Device short name	LA9Z
Product or component type	Distribution block
Quantity per set	Set of 8

Complementary

Complementary		
Poles description	3P	
[le] rated operational current	63 A	
[Ui] rated insulation voltage	690 V	
Mounting mode	Rail	
Cable cross section	1.516 mm²	
Busbar pitch	60 mm	
Width	20 mm	
Height	200 mm	
Depth	89 mm	
Colour	Grey	

Environment

IP degree of protection	IP20	

Packing Units

Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	148 g
Package 1 Height	2 cm
Package 1 width	9 cm
Package 1 Length	20 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	1.26 kg
Package 2 Height	10 cm
Package 2 width	18 cm
Package 2 Length	20.5 cm
Unit Type of Package 3	S03
Number of Units in Package 3	32
Package 3 Weight	5.395 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	[™] REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	