Product data sheet
Characteristics

LV850055SP
Mobile Power Pack - for Micrologic X - spare part

Main

Range	Masterpact
Product or component type	Pocket battery
Device application	Power adaptor
Range compatibility	Masterpact MTZ1 circuit breaker Masterpact MTZ2 circuit breaker Masterpact MTZ3 circuit breaker

Complementary

Enclosure material	ABS/PC
Charging current	1.5 A
Rated voltage	3.7 V
Charging time	5…10 h
IP degree of protection	IP20
Height	23 mm
Width	65 mm
Depth	77 mm
Colour	Black
Standards	UL
Provided equipment	1 instruction sheet
Offer type	Spare part

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.