# LVR07500A40T

# Anti Harmonic detuned reactor 50kvar 190Hz (3.8) 7% 50Hz 400V





Main	
Range	VarPlus
Device short name	DR
Product or component type	Detuned reactor
Network frequency	50 Hz
Reactive power rating	50 kvar for 400 V AC 50 Hz
Network rated voltage	400 V AC 50 Hz
Tuning order	3 8 - 190 Hz - 7 % - 50 Hz

$\sim$ -						1 _	
Сc	۱m	n	$\Box$	m	on	па	r٧
$\sim$	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	$\mathbf{v}$			<b>-</b> 11	щ	ıγ

Complementary	
Power losses (max)	320 W
Value of inductance	0.75 mH
Inductance tolerance	- 5 % to 5 % per phase
Fundamental current rating	72.2 A
RMS current rating	77.9 A
Electrical insulation class	Class H
[Ui] rated insulation voltage	1.1 kV
Dielectric test voltage	4 kV 50 Hz 1 minute
[Imp] maximum permanent current	1.2 x l1
Harmonic current spectrum	3.7 % x l3 38.2 % x l5 13.6 % x l7 4.9 % x l11
Dynamic withstand current	2.2 x lsc
[lth] conventional free air thermal current	2 A at 250 V AC 50 Hz
Type of installation	Indoor installation
Type of cooling	Forced convection
Connections - terminals	Pad terminal
Fixing center	200 x 125 mm
Height	270 mm
Width	260 mm
Depth	200 mm
Net weight	22 kg

### Environment

Standards	IEC 60068	
IP degree of protection	IP00	
Operating altitude	<= 2000 m	
Ambient air temperature for operation	055 °C at <= 1000 m 050 °C at > 10002000 m	
Average ambient air temperature for operation	50 °C at <= 1000 m (average over 24 hours) 40 °C at <= 1000 m (average over 1 year) 45 °C at > 10002000 m (average over 24 hours) 35 °C at > 10002000 m (average over 1 year)	
Climatic withstand	Relative humidity: 2080 % Salt mist (400 V/50 Hz) : 250 hours	

## Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	29 kg
Package 1 Height	40 cm
Package 1 width	53 cm
Package 1 Length	60 cm
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Weight	58 kg
Package 2 Height	50 cm
Package 2 width	80 cm
Package 2 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	