Product data sheet Characteristics

XB5AA3351

Push button, plastic, flush, black,Ø22, spring return, marked DOWN ARROW, 1 NO





Main Range of product Harmony XB5 Product or component Push-button type Device short name XB5 Bezel material Plastic Dark grey plastic Head type Standard Fixing collar material Plastic Mounting diameter 22 mm Sale per indivisible quantity Shape of signaling unit Round head Type of operator Spring return Operator profile Black flush, down arrow (white) Contacts type and 1 NO composition Contact operation Slow-break Connections - terminals Screw clamp terminals, <= 2 x 1.5 mm² with cable

end conforming to EN/IEC 60947-1

Screw clamp terminals, 1 x $0.22...2 \times 2.5 \text{ mm}^2$ without cable end conforming to EN/IEC 60947-1

Complementary

o o in promonenty		
ght 42 mm		
Width	30 mm	
Depth	52 mm	
Terminals description ISO n°1	(13-14)NO	
Net weight	0.037 kg	
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
Contacts usage	Standard contacts	
Positive opening	Without	
Operating travel	2.6 Mm (NO changing electrical state) 4.3 mm (total travel)	
Operating force	3.8 N NO changing electrical state	
Mechanical durability	10000000 cycles	
Tightening torque	0.81.2 N.m conforming to EN 60947-1	
Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver	
Contacts material	Silver alloy (Ag/Ni)	
Short-circuit protection	circuit protection 10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1	
[Ith] conventional free air thermal current	conventional free air thermal current 10 A conforming to EN/IEC 60947-5-1	
[Ui] rated insulation voltage	voltage 600 V (pollution degree 3) conforming to EN/IEC 60947-1	
[Uimp] rated impulse withstand voltage	EN/IEC 60947-1 6 kV	

[le] rated operational current	3 A at 240 V, AC-15, A600 conforming to EN/IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to EN/IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1 1000000 Cycles AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1: appendix C 1000000 Cycles AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1: appendix C 1000000 Cycles AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1: appendix C 1000000 Cycles DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1: appendix C 1000000 cycles DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1: appendix C		
Electrical durability			
Electrical reliability	Λ < 10exp(-6) at 5 V and 1 mA in clean environment conforming to EN/IEC 60947-5-4 Λ < 10exp(-8) at 17 V and 5 mA in clean environment conforming to EN/IEC 60947-5-4		
Device presentation	Complete product		
Customizable	No		
Customizable	0		
Compatibility code	XB5		

Environment

Environment			
Protective treatment	TH		
Ambient air temperature for storage	-4070 °C		
Ambient air temperature for operation	-4070 °C		
Overvoltage category	Class II conforming to IEC 60536		
IP degree of protection	IP66 conforming to IEC 60529 IP67 IP69 IP69K		
NEMA degree of protection	NEMA 13 NEMA 4X		
IK degree of protection	IK03 conforming to IEC 50102		
Standards	CSA C22.2 No 14 JIS C8201-5-1 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C8201-1		
Product certifications	BV GL RINA CSA DNV LROS (Lloyds register of shipping) UL listed		
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6		
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27		

Packing Units

r acking critis	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	36 g
Package 1 Height	3.4 cm
Package 1 width	5.4 cm
Package 1 Length	8.8 cm
Unit Type of Package 2	S03
Number of Units in Package 2	100

Package 2 Weight	4.078 kg	
Package 2 Height	30 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

Offer Sustainability

Sustainable offer status	Green Premium product		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration		
Toxic heavy metal free	Yes		
Mercury free	Yes		
RoHS exemption information	₽¥Yes		
China RoHS Regulation	China RoHS Declaration		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	☑ End Of Life Information		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		


Contractual warranty

•		
Warranty	18 months	
vvairanty	10 months	

Product data sheet Dimensions Drawings

XB5AA3351


Dimensions



- e: clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.
- (1) Additional row of contacts or double contact

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)


Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
 (3) Ø22.5 mm recommended (Ø22.3 0 +0.4) / Ø0.89 in. recommended (Ø0.88 in. 0 +0.016)

Connections	a in mm	a in in.	b in mm	b in in.
By screw clamp terminals or plug-in connector	40	1.57	30	1.18
By Faston connectors	45	1.77	32	1.26
On printed circuit board	30	1.18	30	1.18

Detail of Lug Recess



- Diameter on finished panel or support
- For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- Ø22.5 mm recommended (Ø22.3 $_0$ ^{+0.4}) / Ø0.89 in. recommended (Ø0.88 in. $_0$ ^{+0.016})