

# XB5AD53C0

Selector switch, Harmony XB5, 3 pos 2 pos  
return to center 2 NO screw clamp cp grey



## Main

|                               |                                                                                                                                                                            |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product              | Harmony XB5                                                                                                                                                                |
| Product or component type     | Selector switch                                                                                                                                                            |
| Device short name             | XB5                                                                                                                                                                        |
| Bezel material                | Plastic colour plated grey                                                                                                                                                 |
| Head type                     | Standard                                                                                                                                                                   |
| Mounting diameter             | 22 mm                                                                                                                                                                      |
| Sale per indivisible quantity | 1                                                                                                                                                                          |
| Shape of signaling unit head  | Round                                                                                                                                                                      |
| Type of operator              | To centre spring return                                                                                                                                                    |
| Operator profile              | Black standard handle                                                                                                                                                      |
| Operator position information | 3 positions +/- 45°                                                                                                                                                        |
| Contacts type and composition | 2 NO                                                                                                                                                                       |
| Contact operation             | Slow-break                                                                                                                                                                 |
| Connections - terminals       | Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals, >= 1 x 0.22 mm² without cable end conforming to EN/IEC 60947-1 |

## Complementary

|                                             |                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Height                                      | 42 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Width                                       | 30 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Depth                                       | 70 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Terminals description ISO n°1               | (13-14)NO                                                                                                                                                                                                                                                                                                                                                                      |
| Net weight                                  | 0.052 kg                                                                                                                                                                                                                                                                                                                                                                       |
| Resistance to high pressure washer          | 7000000 Pa at 55 °C, distance : 0.1 m                                                                                                                                                                                                                                                                                                                                          |
| Contacts usage                              | Standard contacts                                                                                                                                                                                                                                                                                                                                                              |
| Positive opening                            | Without                                                                                                                                                                                                                                                                                                                                                                        |
| Torque value                                | 0.14 N.m NO changing electrical state                                                                                                                                                                                                                                                                                                                                          |
| Mechanical durability                       | 1000000 cycles                                                                                                                                                                                                                                                                                                                                                                 |
| Tightening torque                           | 0.8...1.2 N.m conforming to EN 60947-1                                                                                                                                                                                                                                                                                                                                         |
| Shape of screw head                         | Cross compatible with Philips no 1 screwdriver<br>Cross compatible with pozidriv No 1 screwdriver<br>Slotted compatible with flat Ø 4 mm screwdriver<br>Slotted compatible with flat Ø 5.5 mm screwdriver                                                                                                                                                                      |
| Contacts material                           | Silver alloy (Ag/Ni)                                                                                                                                                                                                                                                                                                                                                           |
| Short-circuit protection                    | 10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1                                                                                                                                                                                                                                                                                                                     |
| [Ith] conventional free air thermal current | 10 A conforming to EN/IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                            |
| [Ui] rated insulation voltage               | 600 V (pollution degree 3) conforming to EN 60947-1                                                                                                                                                                                                                                                                                                                            |
| [Uimp] rated impulse withstand voltage      | EN 60947-1 6 kV                                                                                                                                                                                                                                                                                                                                                                |
| [Ie] rated operational current              | 3 A at 240 V, AC-15, A600 conforming to EN/IEC 60947-5-1<br>6 A at 120 V, AC-15, A600 conforming to EN/IEC 60947-5-1<br>0.1 A at 600 V, DC-13, Q600 conforming to EN/IEC 60947-5-1<br>0.27 A at 250 V, DC-13, Q600 conforming to EN/IEC 60947-5-1<br>0.55 A at 125 V, DC-13, Q600 conforming to EN/IEC 60947-5-1<br>1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability  | 1000000 Cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles, DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C |
| Electrical reliability | $\Lambda < 10\exp(-6)$ at 5 V, 1 mA in clean environment conforming to EN/IEC 60947-5-4<br>$\Lambda < 10\exp(-8)$ at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Device presentation    | Complete product                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

## Environment

|                                       |                                                                                                                                                                                |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                                                                             |
| Ambient air temperature for storage   | -40...70 °C                                                                                                                                                                    |
| Ambient air temperature for operation | -40...70 °C                                                                                                                                                                    |
| Electrical shock protection class     | Class II conforming to IEC 60536                                                                                                                                               |
| IP degree of protection               | IP67 conforming to IEC 60529                                                                                                                                                   |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                                                                                                                             |
| IK degree of protection               | IK06 conforming to IEC 50102                                                                                                                                                   |
| Standards                             | EN/IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>EN/IEC 60947-1<br>JIS C8201-5-1<br>JIS C8201-1                                                            |
| Product certifications                | GL<br>UL<br>RINA<br>LROS (Lloyds register of shipping)<br>BV<br>DNV<br>CSA                                                                                                     |
| Vibration resistance                  | 5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                                                                                               |
| Shock resistance                      | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |


## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 51.000 g |
| Package 1 Height | 8.600 cm |
| Package 1 width  | 3.300 cm |
| Package 1 Length | 5.200 cm |

## Offer Sustainability

|                            |                                                                                                                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           |  <a href="#">REACH Declaration</a>                                                                |
| REACH free of SVHC         | Yes                                                                                                                                                                                  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                                                                                                                  |
| Mercury free               | Yes                                                                                                                                                                                  |
| RoHS exemption information |  <a href="#">Yes</a>                                                                              |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>                                                           |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins                                                          |

## Dimensions



e: clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.

## Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

### Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3)  $\varnothing 22.5$  mm recommended ( $\varnothing 22.3 \text{ }_0^{+0.4}$ ) /  $\varnothing 0.89$  in. recommended ( $\varnothing 0.88 \text{ in. }_0^{+0.016}$ )

| Connections                                   | a in mm | a in in. | b in mm | b in in. |
|-----------------------------------------------|---------|----------|---------|----------|
| By screw clamp terminals or plug-in connector | 40      | 1.57     | 30      | 1.18     |
| By Faston connectors                          | 45      | 1.77     | 32      | 1.26     |
| On printed circuit board                      | 30      | 1.18     | 30      | 1.18     |

### Detail of Lug Recess



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3)  $\varnothing 22.5$  mm recommended ( $\varnothing 22.3 \text{ }_0^{+0.4}$ ) /  $\varnothing 0.89$  in. recommended ( $\varnothing 0.88 \text{ in. }_0^{+0.016}$ )