



## Main

|                           |                      |
|---------------------------|----------------------|
| Range of product          | Harmony XAC          |
| Product or component type | Head for push-button |
| Component name            | XACA                 |

## Complementary

|                                       |                                                                  |
|---------------------------------------|------------------------------------------------------------------|
| Marking                               | Unmarked                                                         |
| Operator additional information       | Booted                                                           |
| Cap/operator or lens colour           | White                                                            |
| Product compatibility                 | XACA..                                                           |
| Mounting location                     | Front of enclosure                                               |
| Sale per indivisible quantity         | 10                                                               |
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>EN/IEC 60204-32<br>UL 508 |
| Ambient air temperature for operation | -25...70 °C                                                      |
| Ambient air temperature for storage   | -40...70 °C                                                      |
| Vibration resistance                  | 15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6               |
| Shock resistance                      | 100 gn conforming to IEC 60068-2-27                              |
| Overvoltage category                  | Class II conforming to IEC 61140                                 |
| IP degree of protection               | IP65 conforming to IEC 60529                                     |
| IK degree of protection               | IK08 conforming to EN 50102                                      |
| Net weight                            | 0.01 kg                                                          |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 0.009 kg |
| Package 1 Height | 0.300 dm |
| Package 1 width  | 1.100 dm |
| Package 1 Length | 1.000 dm |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| REACH free of SVHC         | Yes                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                            |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                         |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|