XACB9221

booted head for pushbutton XAC-B - white - 16 mm, -40..+70 $^{\circ}\text{C}$



Main

Range of product	Harmony XAC
Product or component type	Head for push-button
Component name	XACB
Marking	Unmarked
Operator additional information	Booted
Operating travel	16 mm
Cap/operator or lens colour	White
Product compatibility	XESD1191 XESD1181 XESD1291 XESD1281
Sale per indivisible quantity	10

Complementary

Net weight	0.005 kg

Environment

Standards	IEC 60947-5-1	
	EN 60947-5-1	
	CSA C22.2 No 14	
Ambient air temperature for operation	-4070 °C	
Ambient air temperature for storage	-4070 °C	
Vibration resistance	15 gn (f= 10500 Hz) conforming to IEC 60068-2-6	
Shock resistance	100 gn conforming to IEC 60068-2-27	
Electrical shock protection class	Class II conforming to IEC 61140	
IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 50102	

Packing Units

· coming come	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	6 g
Package 1 Height	4 cm
Package 1 width	12 cm
Package 1 Length	12 cm
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Weight	63 g
Package 2 Height	4 cm
Package 2 width	12 cm
Package 2 Length	12 cm
Unit Type of Package 3	S01
Number of Units in Package 3	150
Package 3 Weight	1.15 kg
Package 3 Height	15 cm

Package 3 width	15 cm	
Package 3 Length	40 cm	
Offer Sustainability		

(Offer	Sus	taına	abı	lity
Ξ		L D -			

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	

Contractual warranty

Warranty	18 months