



## Main

|                           |                                                  |
|---------------------------|--------------------------------------------------|
| Range of product          | Harmony Series K                                 |
| Product or component type | Cam switch operating head                        |
| Component name            | KCG                                              |
| Product compatibility     | Front mounting bodies 12 and 20 A by multifixing |
| Cam switch head type      | With front plate 45 x 45 mm                      |
| Type of operator          | Red handle, length = 35 mm                       |
| Rotary handle padlocking  | Without                                          |
| Presentation of legend    | With yellow legend, 0 - 1                        |
| Switching angle           | 90 °                                             |

## Complementary

|                       |                |
|-----------------------|----------------|
| Mechanical durability | 1000000 cycles |
| CAD overall width     | 45 mm          |
| CAD overall height    | 45 mm          |
| CAD overall depth     | 34 mm          |
| Length                | 35 mm          |
| Net weight            | 0.012 kg       |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Protective treatment                  | TC                                                           |
| Ambient air temperature for operation | -25...55 °C                                                  |
| Ambient air temperature for storage   | -40...70 °C                                                  |
| Shock resistance                      | 30 gn conforming to IEC 68-2-27                              |
| Vibration resistance                  | 5 gn conforming to IEC 68-2-6 (f = 10...150 Hz)              |
| IP degree of protection               | IP40 conforming to IEC 529<br>IP40 conforming to NF C 20-010 |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 0.012 kg |
| Package 1 Height | 0.850 dm |
| Package 1 width  | 0.700 dm |
| Package 1 Length | 0.700 dm |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| REACH free of SVHC         | Yes                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                            |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                         |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|