


XVS72BMWN

Harmony XVS, Electronic alarm, white, NPN,
mounting support DIN 72, 0...90 dB, 16 tones,
4 channels, 12...24 V AC/DC



Main

Range of product	Harmony XVS
Product or component type	Electronic alarm
Device short name	XVS

Complementary

Colour	White
Material	ABS (acrylonitrile butadiene-styrene): body PC (polycarbonate): terminal cover
Net weight	0.18 kg
Marking	CE
Overvoltage category	Class II conforming to EN/IEC 61140
Mounting support	72 mm DIN rail
[Us] rated supply voltage	12...24 V DC
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	117 mA at 12 V 125 mA at 24 V 158 mA at 12 V 200 mA at 24 V
Clamping connection capacity	$\leq 1 \times 1.5 \text{ mm}^2$
Width	72 mm
Height	72 mm
Depth	69.3 mm

Environment

Discrete output type	NPN
Signalling type	16 tones alarm
Standards	EN/IEC 61000-6-2 UL 464 EN/IEC 61000-6-3
Product certifications	UR
Protective treatment	TC
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-10...50 °C
IP degree of protection	Panel mounted: IP54 conforming to EN/IEC 60529
Noise level	0...90 dB (continuous or intermittent tone) at 1 m

Packing Units

Package 1 Weight	0.264 kg
Package 1 Height	1.040 dm
Package 1 width	0.940 dm
Package 1 Length	0.940 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Electronic Alarm

Dimensions

