



Main

Range	Masterpact
Product or component type	Ethernet interface module
Condition of use	With specific accessories
Device application	Communication
Device mounting	Embedded

Complementary

Communication gateway	Ethernet TCP/IP to Modbus
Communication network type	ULP, CANopen on USB Ethernet, Ethernet TCP/IP10/100 Mbps on RJ45
Mounting mode	Drawout
Mounting support	DIN rail
Localisation on device	Chassis
Maximum supply current	3 A
Power consumption in W	72 W
Product certifications	CE EAC FCC
Standards	IEC 60950 IACS E10 IEC 60947-6-2
Height	51 mm
Width	51 mm
Depth	52.5 mm
Net weight	0.075 kg
Web server	Embedded
Provided equipment	1 instruction sheet
Offer type	Spare part

Environment

IP degree of protection	IP30
Ambient air temperature for operation	-20...70 °C

Packing Units

Package 1 Weight	0.312 kg
Package 1 Height	0.350 dm
Package 1 width	0.600 dm
Package 1 Length	0.820 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Halogen content performance	Halogen free plastic parts product