



## Main

Range	Masterpact
Product or component type	Ethernet interface module Accessory kit
Device application	Communication
Device mounting	Embedded Direct mounting

## Complementary

Communication gateway	Ethernet TCP/IP to Modbus
Communication network type	ULP, CANopen on USB Ethernet, Ethernet TCP/IP10/100 Mbps on RJ45
Mounting mode	Drawout
Mounting support	DIN rail
Localisation on device	Chassis
Maximum supply current	3 A
Power consumption in W	72 W
Height	51 mm
Width	51 mm
Depth	52.5 mm
Net weight	0.075 kg
Provided equipment	1 instruction sheet
Offer type	Spare part





## Environment

Ambient air temperature for operation	-20...70 °C
---------------------------------------	-------------

## Packing Units

Package 1 Weight	0.151 kg
Package 1 Height	17.000 cm
Package 1 width	30.000 cm
Package 1 Length	45.000 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>