



### Main

Range of product	Altivar
Bus type	CANopen
Accessory / separate part category	Connection accessory
Accessory / separate part type	Tap junction
Accessory / separate part destination	CANopen bus
Quantity per set	Set of 1

### Complementary

Range compatibility	Altivar 31 Altivar Machine ATV340 except Sercos drives Lexium SD3 Modicon M238 Altivar 31C Altivar Process ATV900 Altivar 312 CANopen Altivar Machine ATV320 Modicon M258 Magelis XBT GC, GT/GK with control Modicon LMC058 Altivar 32 Altivar Process ATV600
Communication port protocol	CANopen
Electrical connection	2 connectors RJ45
Net weight	0.48 kg

### Environment

IP degree of protection	IP20
-------------------------	------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	241 g
Package 1 Height	7 cm
Package 1 width	16.6 cm
Package 1 Length	22.7 cm
Unit Type of Package 2	P06
Number of Units in Package 2	56
Package 2 Weight	26.5 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	60 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------