



Main

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for plug and socket
Accessories included with enclosure	1 plate for 50 x 50 power outlets 1 terminal block 4 holes
Mounting plate description	Without mounting plate

Complementary

Enclosure mounting	Surface
Number of 18 mm modules per row	4
Total number of 18 mm modules	4
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	2
Number of plates	1 for 50 x 50 power outlets
Provided equipment	1 plate for 50 x 50 power outlet 1 terminal block 4 holes
Type of front cover	Transparent
Power dissipation in W	6.5 W
[In] rated current	63 A
Number of pre-cutouts PG ISO	1
Number of terminal blocks	1 with 4 outgoers
Distribution block outgoers	2 x 10 mm ² 2 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Base dimension	65 x 85 mm
Width	98 mm
Height	310 mm
Depth	98.5 mm
Internal depth	61 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)
Targeted country	France




Environment

Standards	IEC 60529 IEC 670 EN 50262 IEC 60439-3 EN 50102
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	490 g
Package 1 Height	9 cm
Package 1 width	9 cm
Package 1 Length	31 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	4.92 kg
Package 2 Height	21.5 cm
Package 2 width	34.5 cm
Package 2 Length	40.5 cm
Unit Type of Package 3	P12
Number of Units in Package 3	192
Package 3 Weight	96.096 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------