Product data sheet Characteristics

DE1DS2A04

TeSys LE - enclosure for DOL starter - without pushbuttons





Main

Range of product	TeSys
Range	TeSys
Device short name	DE1D
Product or component type	Enclosure
Material	Polycarbonate
Device composition	Contactor ordered separately Thermal overload relay ordered separately
Product compatibility	LE1D1835
Control type	Without

Complementary

Complementary		
Cable entry number	2 ISO20 top	
	2 ISO20 bottom	
	2 Pg 16 bottom	
	2 ISO25 top	
	2 Pg 21 bottom	
	2 ISO25 bottom	
Height	201 mm	
Width	103 mm	
Depth	145 mm	
Net weight	0.5 kg	

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Ambient air temperature for operation	-540 °C
Environmental characteristic	Standard environment

Packing Units

5	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	766 g
Package 1 Height	16.5 cm
Package 1 width	20 cm
Package 1 Length	25 cm
Unit Type of Package 2	P06
Number of Units in Package 2	22
Package 2 Weight	29.85 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty 18 months	
--------------------	--