

# Product data sheet

## Characteristics

# DE1DS2A13

## TeSys LE - enclosure for DOL starter - with selector switch and pushbutton



### Main

Range of product	TeSys
Range	TeSys
Device short name	DE1D
Product or component type	Enclosure
Material	Polycarbonate
Device composition	Contactor ordered separately Thermal overload relay ordered separately
Product compatibility	LE1D18...35
Control type	Push-button reset blue R Selector switch 2 positions start/stop O-I

### Complementary

Cable entry number	2 ISO20 top 2 ISO20 bottom 2 Pg 16 bottom 2 ISO25 top 2 Pg 21 bottom 2 ISO25 bottom
Height	201 mm
Width	103 mm
Depth	170 mm
Net weight	0.5 kg

### Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Ambient air temperature for operation	-5...40 °C
Environmental characteristic	Standard environment

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	660 g
Package 1 Height	14.5 cm
Package 1 width	16 cm
Package 1 Length	21 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes

---

China RoHS Regulation

 China RoHS Declaration

Environmental Disclosure

 Product Environmental Profile

---

### Contractual warranty

---

Warranty

18 months

---