

Product data sheet

Characteristics

VBFXGE2

TeSys Vario enclosed, empty enclosure for V3-V4, black handle, IP65



Main

Range	TeSys
Device short name	VBFX
Product or component type	Enclosure
Product compatibility	V3 V4

Complementary

Handle colour	Black
Handle front plate colour	Black
Rotary handle padlocking	With
[I]the] conventional enclosed thermal current	50 A 63 A
Environmental characteristic	Standard environment
Height	180 mm
Width	157 mm
Depth	152 mm
Net weight	0.66 kg

Environment

IP degree of protection	IP65
-------------------------	------

Packing Units

Package 1 Weight	0.500 kg
Package 1 Height	1.400 dm
Package 1 width	1.850 dm
Package 1 Length	2.300 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months
----------	-----------
