



Main

Range	Micro Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	8
Nb of horizontal rows	1
Type of door	Reversible Transparent
Width	198 mm
Height	200 mm
Depth	72 mm
Built-in depth	0 mm

Complementary

Enclosure mounting	Surface
9 mm pitches	16
Total number of 18 mm modules	8
Type of rail	DIN
Mounting plate description	Without mounting plate
Enclosure material	Enclosure: self-extinguishing material
Internal depth	66 mm
Colour	Enclosure: white (RAL 9003)
Market segment	Small commercial

Environment

Standards	EN 60439-3 IEC 23-48 IEC 60439-3 IEC 60695-2-1
Fire resistance	650 °C (30 s) conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529 (with installation of devices IP40 minimum)
IK degree of protection	IK07 conforming to EN 50102

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	405 g
Package 1 Height	7.5 cm
Package 1 width	20 cm
Package 1 Length	20 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	14
Package 2 Weight	6.17 kg
Package 2 Height	24 cm
Package 2 width	40 cm
Package 2 Length	59.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------