

Main

Range	Prisma
Range of product	Prisma G Prisma P
Product or component type	Insulated flexible bar
Product name	Prisma G enclosure Prisma P enclosure Prisma iPM L enclosure Prisma iPM M enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA



Complementary

Installation description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[I _e] rated operational current	200 A
[I _n] rated current	200 A
Busbar cross section	20 x 2 mm
Length	1800 mm
Net weight	1.38 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.2 kg
Package 1 Height	2 cm
Package 1 width	9 cm
Package 1 Length	192 cm
Unit Type of Package 2	P2M
Number of Units in Package 2	130
Package 2 Weight	179.4 kg
Package 2 Height	35 cm
Package 2 width	120 cm
Package 2 Length	200 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile