Product data sheet Characteristics

88082 SIDE CONN. BLOCK NSX630 3P















Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection transfer assembly
Product name	Prisma P enclosure

Complementary

Poles description	3P	
Installation description	Cubicle - width 600 mm	
Installed device	Prisma: withdrawable Polyfast - side connection ComPact: NSX400630	
[le] rated operational current	630 A	
[In] rated current	630 A	
Colour	Stainless steel	
Height	145 mm	
Width	220 mm	
Depth	55 mm	
Quantity per set	Set of 1	

Packing Units

r doming ormo		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	3.4 kg	
Package 1 Height	15 cm	
Package 1 width	18 cm	
Package 1 Length	23 cm	
Unit Type of Package 2	S04	
Number of Units in Package 2	4	
Package 2 Weight	25.84 kg	
Package 2 Height	30 cm	
Package 2 width	40 cm	
Package 2 Length	60 cm	
Unit Type of Package 3	P12	
Number of Units in Package 3	12	
Package 3 Weight	320.08 kg	
Package 3 Height	80 cm	
Package 3 width	80 cm	
Package 3 Length	120 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	