



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection transfer assembly
Product name	Prisma P enclosure PC

Complementary

Poles description	4P
Installation description	Cubicle - width 600 mm
Installed device	ComPact: NSX400...630 Prisma: withdrawable Polyfast - rear connection
[Ie] rated operational current	630 A
[In] rated current	630 A
Colour	Stainless steel
Height	145 mm
Width	220 mm
Depth	55 mm
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.5 kg
Package 1 Height	17 cm
Package 1 width	20 cm
Package 1 Length	23 cm
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Weight	10 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	8
Package 3 Weight	32 kg
Package 3 Height	50 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile