



**Main**

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	1P + N
[I <sub>th</sub> ] conventional free air thermal current	16 A
I <sup>2</sup> t on activation	100000 A <sup>2</sup> .s
Number of points	1
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable length	0.2 m
Quantity per set	Set of 6

**Complementary**

[Ui] rated insulation voltage	600 V conforming to CSA 600 V conforming to UL 690 V conforming to IEC 60439-1
Peak current	25 kA
Width	18 mm
Height	46 mm
Depth	38 mm
Net weight	0.035 kg

**Environment**

Standards	IEC 60439
Product certifications	DNV UL LROS (Lloyds register of shipping) CSA

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	28 g
Package 1 Height	4 cm
Package 1 width	11 cm
Package 1 Length	6.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Weight	234 g
Package 2 Height	13.6 cm
Package 2 width	15.8 cm
Package 2 Length	12.8 cm
Unit Type of Package 3	S04
Number of Units in Package 3	96
Package 3 Weight	4.598 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------