



Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	1P + N
[I _{th}] conventional free air thermal current	25 A
I ² t on activation	200000 A ² .s
Number of cables	2 cable(s) 4 mm ² at 105 °C
Width	54 mm
Height	190 mm
Depth	61 mm

Complementary

[Ui] rated insulation voltage	690 V conforming to IEC 60439-1
Electrical connection	Connector
9 mm pitches	6
Net weight	0.23 kg

Environment

Standards	IEC 60439
Product certifications	DNV UL CSA LROS (Lloyds register of shipping)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	357 g
Package 1 Height	6.5 cm
Package 1 width	7.5 cm
Package 1 Length	22 cm
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Weight	4.052 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	160
Package 3 Weight	72.9 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------