



### Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	3P
[I <sub>th</sub> ] conventional free air thermal current	25 A
I <sup>2</sup> t on activation	200000 A <sup>2</sup> .s
Number of cables	3 cable(s) 4 mm <sup>2</sup> at 105 °C
Width	54 mm
Height	105 mm
Depth	61 mm

### Complementary

[Ui] rated insulation voltage	690 V conforming to IEC 60439-1
9 mm pitches	6
Net weight	0.145 kg

### Environment

Standards	IEC 60439
Product certifications	DNV LROS (Lloyds register of shipping) UL CSA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	224 g
Package 1 Height	6.5 cm
Package 1 width	7.5 cm
Package 1 Length	13.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	40
Package 2 Weight	9.496 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	320
Package 3 Weight	85.884 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------