



Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	3P
[I _{th}] conventional free air thermal current	25 A
I ² t on activation	200000 A ² .s
Number of cables	3 cable(s) 4 mm ² at 105 °C
Width	106 mm
Height	190 mm
Depth	63 mm

Complementary

[Ui] rated insulation voltage	690 V conforming to IEC 60439-1
9 mm pitches	12
Net weight	0.61 kg

Environment

Standards	IEC 60439
Product certifications	CSA LR0S (Lloyds register of shipping) UL DNV

Packing Units

Package 1 Weight	0.815 kg
Package 1 Height	0.730 dm
Package 1 width	1.250 dm
Package 1 Length	2.050 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------