



Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	3P + Nc
[I _{th}] conventional free air thermal current	50 A
I ² t on activation	200000 A ² .s
Number of cables	3 cable(s) 4 mm ² at 105 °C 1 cable(s) 1.5 mm ² 3 cable(s) 4 mm ²
Width	106 mm
Height	190 mm
Depth	63 mm

Complementary

[Ui] rated insulation voltage	690 V conforming to IEC 60439-1
9 mm pitches	12
Net weight	0.71 kg

Environment

Standards	IEC 60439
Product certifications	DNV LROS (Lloyds register of shipping) CSA UL

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	809 g
Package 1 Height	9.1 cm
Package 1 width	11.5 cm
Package 1 Length	23.7 cm
Unit Type of Package 2	S03
Number of Units in Package 2	9
Package 2 Weight	8.055 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------