



Main

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	3P + Nc
[I _{th}] conventional free air thermal current	10 A common mode 16 A
I ² t on activation	100000 A ² .s
Number of points	2
Number of cables	1 cable(s) 1.5 mm ² 3 cable(s) 2.5 mm ²
Cable length	0.2 m
Quantity per set	Set of 6

Complementary

[Ui] rated insulation voltage	600 V conforming to CSA 600 V conforming to UL 690 V conforming to IEC 60439-1
Peak current	25 kA
Electrical connection	Connector
Width	36 mm
Height	46 mm
Depth	38 mm
Net weight	0.045 kg

Environment

Standards	IEC 60439
Product certifications	DNV LR0S (Lloyds register of shipping) UL CSA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	54 g
Package 1 Height	12.5 cm
Package 1 width	13 cm
Package 1 Length	15.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Weight	391 g
Package 2 Height	12.5 cm
Package 2 width	13 cm
Package 2 Length	15.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	90
Package 3 Weight	7.06 kg
Package 3 Height	30 cm

Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------