



### Main

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	2P
[I <sub>th</sub> ] conventional free air thermal current	32 A
I <sup>2</sup> t on activation	200000 A <sup>2</sup> .s
Number of points	1
Number of cables	2 cable(s) 4 mm <sup>2</sup>
Cable length	1 m
Quantity per set	Set of 6

### Complementary

[U <sub>i</sub> ] rated insulation voltage	600 V conforming to CSA 600 V conforming to UL 690 V conforming to IEC 60439-1
Peak current	25 kA
Width	18 mm
Height	46 mm
Depth	38 mm
Net weight	0.04 kg

### Environment

Standards	IEC 60439
Product certifications	UL DNV LROS (Lloyds register of shipping) CSA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	119 g
Package 1 Height	8.6 cm
Package 1 width	22.2 cm
Package 1 Length	23 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Weight	718 g
Package 2 Height	8.6 cm
Package 2 width	22.2 cm
Package 2 Length	23 cm
Unit Type of Package 3	S04
Number of Units in Package 3	54
Package 3 Weight	7.844 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------