



Main

Range	Multi 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	2L
Length in 18 mm modules	12

Complementary

Number of ways	6 ways 2 L
Poles configuration for 1 way	1 x 2P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	36 mm
Marking	L1 L2
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	100 A at 40 °C
[Ue] rated operational voltage	277 V AC Ph/N 480 V AC Ph/Ph
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Width	216 mm
Colour	Light grey (RAL 7035)
Range compatibility	Multi 9 C60SP

Environment

Standards	IEC 60947-2 GB 14048.2 UL 1077
Fire resistance	960 °C (30 s)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	96 g
Package 1 Height	1.3 cm
Package 1 width	5.5 cm
Package 1 Length	21.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	144

Package 2 Weight	14.418 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------