



Main

Range	Multi 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	48

Complementary

Number of ways	13 ways Aux + 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	63 mm
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to UL 508
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	96
Width	864 mm
Colour	Light grey (RAL 7035)
Range compatibility	Multi 9 C60BP

Environment

Standards	UL 508
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3
IP degree of protection	IP20 with end-pieces and tooth covers

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.174 kg
Package 1 Height	2.1 cm
Package 1 width	6.2 cm
Package 1 Length	100.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	6.161 kg

Package 2 Height	10 cm
Package 2 width	12 cm
Package 2 Length	108 cm
Unit Type of Package 3	P12
Number of Units in Package 3	35
Package 3 Weight	55.127 kg
Package 3 Height	112 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins