



Main

Range	Prisma
Product or component type	Mounting plate fixed part
Product specific application	Motor-control feeder

Complementary

Enclosure/cubicle description	Cubicle
Enclosure/cubicle width	650 mm
Height	150 mm
Installed device	GS1-F + 2LC1-D09 to 25 2 speed with switch-disconnector fuse + contactor + thermal protection GS1-F + LC1-D09 to 80 non reversing with switch-disconnector fuse + contactor + thermal protection GS1-F + LC2-D09 to 25 reversing with switch-disconnector fuse + contactor + thermal protection GV2-L + 2LC1-D09 to D32 2 speed with circuit-breaker + contactor + thermal protection GV2-L + LC1-D09 to D32 non reversing with circuit-breaker + contactor + thermal protection GV2-L + LC1-D40 to D50 non reversing with circuit-breaker + contactor + thermal protection GV2-L + LC2-D09 to D32 reversing with circuit-breaker + contactor + thermal protection NS80HMA + LC1-D50 to D65 non reversing with circuit-breaker + contactor + thermal protection NS80HMA + LC1-D80 non reversing with circuit-breaker + contactor + thermal protection
Mounting mode	Disconnectable
Number of vertical modules [50 mm]	3
Colour	White
Colour code	RAL 9001
Special colour options	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.84 kg
Package 1 Height	16.5 cm
Package 1 width	21 cm
Package 1 Length	66 cm
Unit Type of Package 2	P12
Number of Units in Package 2	32
Package 2 Weight	90.88 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------