LV432623

PLATINE COMPACT NSX 400-630 3P IEC/UL FOR 60 BUSBARS INTERAXIS





Main	
Range	Linergy
Product name	BZ
Device short name	LA9Z

Adaptors for busbar systems

Number of ways 1 way

Product or component

type

Complementary

Range compatibility	Prisma G
	Prisma P
	Prisma PH
	Spacial
	ComPact
Product compatibility	NSX400630
	PowerPact NL
Poles description	3P
Permissible current	200 A - busbar cross section: 12 x 5 mm
	250 A - busbar cross section: 15 x 5 mm
	320 A - busbar cross section: 20 x 5 mm
	400 A - busbar cross section: 25 x 5 mm
	450 A - busbar cross section: 30 x 5 mm
	360 A - busbar cross section: 12 x 10 mm
	520 A - busbar cross section: 20 x 10 mm
	630 A - busbar cross section: 30 x 10 mm
[Ui] rated insulation voltage	690 V
Busbar pitch	60 mm
Width	139 mm
Height	270 mm
Depth	63 mm
Colour	Anthracite grey

Environment

IP degree of protection	IP20 conforming to IEC 60529	

Packing Units

PCE	
1	
2.068 kg	
7 cm	
14.5 cm	
31.5 cm	
-	1 2.068 kg 7 cm 14.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins