



Main

Range	Linergy
Product name	BZ
Device short name	LA9Z
Product or component type	Adaptors for busbar systems
Number of ways	1 way

Complementary

Range compatibility	Prisma G Prisma P Prisma PH Spacial ComPact
Product compatibility	NSX400...630
Poles description	4P
Permissible current	200 A - busbar cross section: 12 x 5 mm 250 A - busbar cross section: 15 x 5 mm 320 A - busbar cross section: 20 x 5 mm 400 A - busbar cross section: 25 x 5 mm 450 A - busbar cross section: 30 x 5 mm 360 A - busbar cross section: 12 x 10 mm 520 A - busbar cross section: 20 x 10 mm 630 A - busbar cross section: 30 x 10 mm
[Ui] rated insulation voltage	690 V
Busbar pitch	60 mm
Width	184 mm
Height	284 mm
Depth	63 mm
Colour	Anthracite grey

Environment

IP degree of protection	IP20 conforming to IEC 60529
-------------------------	------------------------------

Packing Units

Package 1 Weight	2.870 kg
Package 1 Height	0.850 dm
Package 1 width	1.950 dm
Package 1 Length	3.300 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins