
Product data sheet Characteristics

LV847432

PF ready-to-close contact - 5 A/240 VAC - for MTZ1 - drawout



Main

IVIAIII	
Range	Masterpact
Device short name	PF
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	Masterpact MTZ1 circuit breaker

Complementary

Standard	
1 NO/NC	
Drawout	
2 A AC-12 480 V AC 50/60 Hz	
3 A DC-12 24/48 V DC	
0.3 A DC-12 125 V DC	
0.15 A DC-12 250 V DC	
5 A AC-12 240/380 V AC 50/60 Hz	
100 mA at 24 V	
	1 NO/NC Drawout 2 A AC-12 480 V AC 50/60 Hz 3 A DC-12 24/48 V DC 0.3 A DC-12 125 V DC 0.15 A DC-12 250 V DC 5 A AC-12 240/380 V AC 50/60 Hz

Packing Units

r doming orms		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	42 g	
Package 1 Height	1.3 cm	
Package 1 width	4.7 cm	
Package 1 Length	6.5 cm	

Offer Sustainability

REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interactive for and is not to be used for determining suitability or intensity of these products for specific user applications. It is the dourn and resting of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or itable for misuse of the information contained herein.