

Product data sheet

Characteristics

33108

auxiliary contact - NO/NC standard -

NS1600b..3200 NS630b..1600



Main

Product or component type	Auxiliary contact
Device short name	OF
Device application	Breaker status monitoring
Range compatibility	ComPact NS630b..1600 ComPact NS1600b..3200
Signal contacts composition	1 NO/NC

Complementary

Local signalling	ON/OFF indication for open/close
Auxiliary contacts type	Standard
Mounting mode	Clip-on
[Ith] conventional free air thermal current	6 A
[Ie] rated operational current	AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 220/240 V AC 50/60 Hz AC-12: 6 A at 380/440 V AC 50/60 Hz AC-12: 6 A at 480 V AC 50/60 Hz AC-12: 6 A at 660/690 V AC 50/60 Hz AC-15: 6 A at 24 V AC 50/60 Hz AC-15: 6 A at 48 V AC 50/60 Hz AC-15: 5 A at 110 V AC 50/60 Hz AC-15: 4 A at 220/240 V AC 50/60 Hz AC-15: 2 A at 380/440 V AC 50/60 Hz AC-15: 1.5 A at 480 V AC 50/60 Hz AC-15: 0.1 A at 660/690 V AC 50/60 Hz DC-12: 6 A at 24 V DC DC-12: 2.5 A at 48 V DC DC-12: 0.6 A at 110 V DC DC-12: 0.3 A at 250 V DC DC-14: 1 A at 24 V DC DC-14: 0.2 A at 48 V DC DC-14: 0.05 A at 110 V DC DC-14: 0.03 A at 250 V DC
Minimum load	100 mA at 24 V DC

Packing Units

Package 1 Weight	0.700 kg
Package 1 Height	0.200 dm
Package 1 width	0.400 dm
Package 1 Length	0.500 dm

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information

Yes

China RoHS Regulation

China RoHS Declaration

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

18 months
