



Main

| | |
|-----------------------------|---|
| Product or component type | Auxiliary contact |
| Device short name | OF |
| Device application | Breaker status monitoring |
| Range compatibility | ComPact NS630b...1600 ComPact NS1600b...3200 |
| Signal contacts composition | 1 NO/NC |

Complementary

| | |
|--|--|
| Local signalling | ON/OFF indication for open/close |
| Auxiliary contacts type | Low level |
| Mounting mode | Clip-on |
| [I _{th}] conventional free air thermal current | 5 A |
| [I _e] rated operational current | AC-12: 5 A at 24 V AC 50/60 Hz AC-12: 5 A at 48 V AC 50/60 Hz AC-12: 5 A at 110 V AC 50/60 Hz AC-12: 5 A at 220/240 V AC 50/60 Hz AC-12: 5 A at 380/440 V AC 50/60 Hz AC-12: 5 A at 480 V AC 50/60 Hz AC-15: 3 A at 24 V AC 50/60 Hz AC-15: 3 A at 48 V AC 50/60 Hz AC-15: 2.5 A at 110 V AC 50/60 Hz AC-15: 2 A at 220/240 V AC 50/60 Hz AC-15: 1.5 A at 380/440 V AC 50/60 Hz AC-15: 1 A at 480 V AC 50/60 Hz DC-12: 5 A at 24 V DC DC-12: 2.5 A at 48 V DC DC-12: 0.6 A at 110 V DC DC-12: 0.3 A at 250 V DC DC-14: 1 A at 24 V DC DC-14: 0.2 A at 48 V DC DC-14: 0.05 A at 110 V DC DC-14: 0.03 A at 250 V DC |
| Minimum load | 1 mA at 4 V DC |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.700 kg |
| Package 1 Height | 0.200 dm |
| Package 1 width | 0.400 dm |
| Package 1 Length | 0.500 dm |

Offer Sustainability

| | |
|----------------------------|--------------------------------|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |

| | |
|-----------------------|---|
| China RoHS Regulation | China RoHS Declaration |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
