




Main

Product or component type	Auxiliary contact
Device short name	SDE
Device application	Breaker status monitoring
Range compatibility	ComPact NS630b...1600
Signal contacts composition	1 NO/NC

Complementary

Fault type	General electric fault
Local signalling	Fault trip for electrical fault
Auxiliary contacts type	Low level
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	5 A
[I _e] rated operational current	AC-12: 5 A at 24 V AC 50/60 Hz AC-12: 5 A at 48 V AC 50/60 Hz AC-12: 5 A at 110 V AC 50/60 Hz AC-12: 5 A at 220/240 V AC 50/60 Hz AC-12: 5 A at 380/440 V AC 50/60 Hz AC-12: 5 A at 480 V AC 50/60 Hz AC-15: 3 A at 24 V AC 50/60 Hz AC-15: 3 A at 48 V AC 50/60 Hz AC-15: 2.5 A at 110 V AC 50/60 Hz AC-15: 2 A at 220/240 V AC 50/60 Hz AC-15: 1.5 A at 380/440 V AC 50/60 Hz AC-15: 1 A at 480 V AC 50/60 Hz DC-12: 5 A at 24 V DC DC-12: 2.5 A at 48 V DC DC-12: 0.6 A at 110 V DC DC-12: 0.3 A at 250 V DC DC-14: 1 A at 24 V DC DC-14: 0.2 A at 48 V DC DC-14: 0.05 A at 110 V DC DC-14: 0.03 A at 250 V DC
Minimum load	1 mA at 4 V DC
Accessory / separate part category	Spare part for Compact NS630b...1600

Packing Units

Package 1 Weight	0.037 kg
Package 1 Height	2.000 cm
Package 1 width	5.000 cm
Package 1 Length	20.000 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------