



Main

Product or component type	Auxiliary contact
Device short name	OF
Device application	Breaker status monitoring
Range compatibility	ComPact NS630b...1600
Signal contacts composition	1 NO/NC

Complementary

Local signalling	ON/OFF indication for open/close
Auxiliary contacts type	Low level
Mounting mode	Clip-on
[Ith] conventional free air thermal current	5 A
[Ie] rated operational current	AC-12: 5 A at 24 V AC 50/60 Hz AC-12: 5 A at 48 V AC 50/60 Hz AC-12: 5 A at 110 V AC 50/60 Hz AC-12: 5 A at 220/240 V AC 50/60 Hz AC-12: 5 A at 380/440 V AC 50/60 Hz AC-12: 5 A at 480 V AC 50/60 Hz AC-15: 3 A at 24 V AC 50/60 Hz AC-15: 3 A at 48 V AC 50/60 Hz AC-15: 2.5 A at 110 V AC 50/60 Hz AC-15: 2 A at 220/240 V AC 50/60 Hz AC-15: 1.5 A at 380/440 V AC 50/60 Hz AC-15: 1 A at 480 V AC 50/60 Hz DC-12: 5 A at 24 V DC DC-12: 2.5 A at 48 V DC DC-12: 0.6 A at 110 V DC DC-12: 0.3 A at 250 V DC DC-14: 1 A at 24 V DC DC-14: 0.2 A at 48 V DC DC-14: 0.05 A at 110 V DC DC-14: 0.03 A at 250 V DC
Minimum load	1 mA at 4 V DC
Accessory / separate part category	Spare part for Compact NS630b...1600

Packing Units

Package 1 Weight	0.088 kg
Package 1 Height	2.000 cm
Package 1 width	5.000 cm
Package 1 Length	15.000 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information

Yes

China RoHS Regulation

China RoHS Declaration

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

18 months
