

Product data sheet

Characteristics

16940

auxiliary contact - 1 NC + 1 OC - 380..415 V - 6 A - for RCCB



Main

Range of product	Multi 9
Product or component type	OC contact
Device short name	OFSP
Signal contacts composition	1 C/O 1 NC
[In] rated current	3 A: 380...415 V AC - 50/60 Hz 6 A: 220...240 V AC - 50/60 Hz 1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC

Complementary

Mounting mode	Fixed
Mounting support	DIN rail
Connections - terminals	Tunnel type terminal 2 cable(s) 1...1.5 mm ² - flexible Tunnel type terminal 2 cable(s) 1...1.5 mm ² - rigid
Tightening torque	0.8 N.m

Environment

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	52 g
Package 1 Height	2.7 cm
Package 1 width	8.1 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	45
Package 2 Weight	2.746 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes

China RoHS Regulation

 China RoHS Declaration

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

18 months
