

# Product data sheet

## Characteristics

19072

auxiliary contact - 1 OC + 1 SD - 6 A - 220..240 V - for NG125



## Main

Range of product	Acti 9
Product or component type	OC and fault contact
Device short name	OF and SD
Signal contacts composition	2 C/O
[In] rated current	3 A: 415 V AC - 50/60 Hz 6 A: <= 240 V AC - 50/60 Hz 1 A: 130 V DC 3 A: <= 48 V DC
9 mm pitches	1

## Complementary

Range compatibility	Acti 9 NG125NA Acti 9 NG125LMA Acti 9 NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Mounting mode	Fixed
Mounting support	DIN rail
Height	102.8 mm
Width	15.3 mm
Depth	75.5 mm
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal1 cable(s) 0.5...2.5 mm <sup>2</sup> - rigid Plate terminal1 cable(s) 0.5...1.5 mm <sup>2</sup> - flexible Plate terminal1 cable(s) 0.5...1.5 mm <sup>2</sup> - flexible with ferrule Plate terminal2 cable(s) 2.5 mm <sup>2</sup> - rigid Plate terminal2 cable(s) 2.5 mm <sup>2</sup> - flexible Plate terminal2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

## Environment

Standards	EN/IEC 60947-5-1
Product certifications	LCIE KEMA ASEFA ASTA
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	66 g
Package 1 Height	2.3 cm
Package 1 width	7.8 cm

Package 1 Length	10.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	9
Package 2 Weight	657 g
Package 2 Height	12 cm
Package 2 width	9 cm
Package 2 Length	24 cm
Unit Type of Package 3	S03
Number of Units in Package 3	81
Package 3 Weight	6.317 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------