



Main

Device short name	Carriage switch
Product or component type	Auxiliary contact
Device application	Monitoring
Range compatibility	MasterPact NT Masterpact NW Masterpact NW DC ComPact NS630b...1600
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Connected position Test position Disconnected position
Mounting mode	Drawout
[Ie] rated operational current	AC-12: 6 A at 690 V AC 50/60 Hz AC-12: 8 A at 240 V AC 50/60 Hz AC-12: 8 A at 380 V AC 50/60 Hz AC-12: 8 A at 480 V AC 50/60 Hz DC-12: 0.3 A at 250 V DC DC-12: 0.8 A at 125 V DC DC-12: 2.5 A at 24/48 V DC
Minimum load	100 mA at 24 V
Accessory / separate part category	Spare part for Masterpact NT Spare part for Masterpact NW Spare part for Masterpact NW DC Spare part for ComPact NS630b...1600

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20 g
Package 1 Height	0.9 cm
Package 1 width	4.7 cm
Package 1 Length	5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	100
Package 2 Weight	3 kg
Package 2 Height	19 cm
Package 2 width	7 cm
Package 2 Length	37 cm
Unit Type of Package 3	S03
Number of Units in Package 3	600
Package 3 Weight	12.4 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------