

Product data sheet

Characteristics

33754

low level carriage switch, drawout circuit breaker, chassis in connected position (CE), 1 changeover contact type



Main

Device short name	Connected position contact
Product or component type	Auxiliary contact
Device application	Monitoring
Range compatibility	MasterPact NT Masterpact NW Masterpact NW DC ComPact NS630b...1600
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Low level
Auxiliary contacts operation	Connected position
Mounting mode	Drawout
[Ie] rated operational current	DC-12: 0.3 A at 250 V DC DC-12: 0.8 A at 125 V DC DC-12: 2.5 A at 24/48 V DC AC-12: 5 A at 24/48 V AC 50/60 Hz AC-12: 5 A at 240 V AC 50/60 Hz AC-12: 5 A at 380 V AC 50/60 Hz
Minimum load	2 mA at 15 V

Offer Sustainability

REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------