



Main

| | |
|--|----------------------------------|
| Range | FuPact |
| Product or component type | Auxiliary contact |
| Device application | Remote indication |
| Range compatibility | ISFT100 fuse-switch disconnecter |
| Auxiliary contacts type | Standard |
| Contact function | Changeover contact |
| Signal contacts composition | 1 NO/NC |
| [I _{th}] conventional free air thermal current | 2 A |

Complementary

| | |
|--|--|
| Output contact breaking capacity | AC-12: 2 A at 24 V AC-12: 2 A at 48 V AC-12: 2 A at 110 V AC-12: 2 A at 220/240 V DC-12: 0.2 A at 24 V DC-12: 0.2 A at 48 V DC-12: 0.2 A at 110 V DC-12: 0.2 A at 220/240 V |
| Minimum load | 100 mA at 24 V |
| [U _i] rated insulation voltage | 250 V |
| Kit composition | Mounting accessory |
| Standards | IEC 60947-5-1 |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 5 g |
| Package 1 Height | 0.7 cm |
| Package 1 width | 10 cm |
| Package 1 Length | 12 cm |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Weight | 487 g |
| Package 2 Height | 15 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|