



## Main

Range	FuPact
Product or component type	Auxiliary contact
Device application	Remote indication
Range compatibility	ISFT100N fuse-switch disconnecter ISFT160 fuse-switch disconnecter
Auxiliary contacts type	Standard
Contact function	Changeover contact
Signal contacts composition	1 NO/NC
[I <sub>th</sub> ] conventional free air thermal current	2 A



## Complementary

Mounting mode	Top mounted
Output contact breaking capacity	AC-12: 6 A at 24 V AC-12: 6 A at 48 V AC-12: 6 A at 110 V AC-12: 6 A at 220/240 V DC-12: 3 A at 24 V DC-12: 1 A at 48 V DC-12: 0.5 A at 110 V DC-12: 0.25 A at 220/240 V
Minimum load	100 mA at 24 V
[U <sub>i</sub> ] rated insulation voltage	250 V
Standards	IEC 60947-5-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5 g
Package 1 Height	0.6 cm
Package 1 width	2.3 cm
Package 1 Length	2.2 cm
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Weight	885 g
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------