



Main

Range	FuPact
Product or component type	Auxiliary contact
Device application	Remote indication
Range compatibility	ISFT250 fuse-switch disconnecter ISFT400 fuse-switch disconnecter ISFT630 fuse-switch disconnecter
Auxiliary contacts type	Standard
Contact function	Changeover contact
Signal contacts composition	1 NO/NC
[I _{th}] conventional free air thermal current	2 A





Complementary

Output contact breaking capacity	AC-12: 2 A at 24 V AC-12: 2 A at 48 V AC-12: 2 A at 110 V AC-12: 2 A at 220/240 V DC-12: 0.2 A at 24 V DC-12: 0.2 A at 48 V DC-12: 0.2 A at 110 V DC-12: 0.2 A at 220/240 V
Minimum load	100 mA at 24 V
[U _i] rated insulation voltage	250 V
Kit composition	Housing
Standards	IEC 60947-5-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7 g
Package 1 Height	1.8 cm
Package 1 width	10 cm
Package 1 Length	19 cm
Unit Type of Package 2	S02
Number of Units in Package 2	100
Package 2 Weight	1.05 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile