

# Product data sheet

## Characteristics

# LV833170SP

CE/CD/CT position contact - 8 A/240 VAC - for  
MTZ/NT/NW drawout - spare part



### Main

Range	Masterpact
Device short name	CE/CD/CT
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	Masterpact MTZ1 circuit breaker Masterpact MTZ2 circuit breaker Masterpact MTZ3 circuit breaker
Signal contacts composition	1 NO/NC

### Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Test position Disconnected position Connected position
Mounting mode	Drawout
[Ie] rated operational current	AC-12: 6 A at 690 V AC 50/60 Hz AC-12: 8 A at 240 V AC 50/60 Hz AC-12: 8 A at 380 V AC 50/60 Hz AC-12: 8 A at 480 V AC 50/60 Hz DC-12: 0.3 A at 250 V DC DC-12: 0.8 A at 125 V DC DC-12: 2.5 A at 24/48 V DC
Minimum load	100 mA at 24 V
Provided equipment	1 instruction sheet
Offer type	Spare part

### Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>