



### Main

Range of product	Acti 9 Clario Prodis Librio
Product or component type	OC contact
Device short name	OFS
Signal contacts composition	1 C/O
[In] rated current	3 A: 380...415 V AC - 50/60 Hz 6 A: 220...240 V AC - 50/60 Hz 1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC
9 mm pitches	1

### Complementary

Range compatibility	Acti 9 RCCB-ID Acti 9 ID C40 Acti 9 IDc Acti 9 ITG40
Mounting mode	Fixed
Mounting support	DIN rail
Height	85.3 mm
Width	9 mm
Depth	78.5 mm
Net weight	33 g
Colour	White
Connections - terminals	Clamp terminal (bottom) 2 cable(s) 1.5 mm <sup>2</sup> - flexible Clamp terminal (bottom) 1 cable(s) 0.5...2.5 mm <sup>2</sup> - rigid Clamp terminal (bottom) 2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

### Environment




Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	0.95 % at 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	42 g
Package 1 Height	2 cm
Package 1 width	7.8 cm
Package 1 Length	9.3 cm

Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	631 g
Package 2 Height	10 cm
Package 2 width	9 cm
Package 2 Length	26 cm
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	5.688 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

### Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------