

# LA2KT2E

Electronic time delay auxiliary contact block,  
TeSys K, 1C/O, on delay 1-30s, front, control  
24-48 V AC/DC



## Main

Range	TeSys
Product name	TeSys K
Product or component type	Time delay auxiliary contact block
Device short name	LA1
Range compatibility	TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K
Mounting location	Front
Pole contact composition	1 C/O
Contacts operation	Time delay
Timer type	On delay
Time delay range	1...30 s
[Ue] rated operational voltage	24...48 V AC/DC for control circuit 240 V AC for signalling circuit
Rated operational voltage limits	0.85...1.1 U <sub>c</sub>
[I <sub>th</sub> ] conventional free air thermal current	2 A for signalling circuit
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1

## Complementary

Reset time	1.5 S during time delay 0.5 s after time delay
Insulation resistance	> 10 MOhm
Connections - terminals	Slip-on terminals
Height	27 mm
Width	38 mm
Depth	38 mm
Net weight	0.04 kg

## Environment

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-10...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	41 g
Package 1 Height	4.8 cm
Package 1 width	4.8 cm
Package 1 Length	5 cm

Unit Type of Package 2	S02
Number of Units in Package 2	70
Package 2 Weight	3.11 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins