

Product data sheet

Characteristics

TRV00121

front display module - FDM 121 - 96 x 96 mm -
IP54



Main

Device short name	FDM121
Product or component type	Display module
Accessory / separate part category	Display and signalling accessory
Range compatibility	Masterpact NW MasterPact NT ComPact NSX ComPact NS630b...1600 ComPact NS1600b...3200 PowerPact H PowerPact J PowerPact L PowerPact P PowerPact R
Product name	Enerlin'X FDM
Function of module	Remote control View network Metering Display alarm

Complementary

Control type	Remote control
Mounting mode	Flush mounting
Mounting support	Surface mount with kit Door cut-out
Display type	LCD screen with white backlighting
Display resolution	128 x 128 pixels
View angle horizontal x vertical	60 x 30°
[Us] rated supply voltage	24 V DC - 20...10 %
Current consumption	21 mA
Standards	CE CSA UL
Height	96 mm
Width	96 mm
Depth	33.6 mm
Accessory / separate part category	Spare part for ComPact NS630b...1600 Spare part for ComPact NS1600b...3200

Environment

IP degree of protection	IP54 front face:
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Package 1 Weight	0.239 kg
Package 1 Height	5.700 cm
Package 1 width	10.200 cm
Package 1 Length	10.200 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------